



TX-10 LS PACKAGE

KEY FEATURES:

- Capable of handling a 20' rod pull
- Heavy-duty construction, ensuring longevity and reliability in demanding applications
- Enhanced diameter featuring a double sheave for increased strength and stability
- Telescopic tower
- 312 steel cat track
- Hydraulic leveling cylinders
- Remote operation
- Drop-down walkways

DRILL SPECIFICATIONS

STROKE LENGTH	132" Feed Stroke
FUEL CAPACITY	250L double-walled fuel tank
ENGINE	Tier 4 Cummins Turbo Diesel 180 Horsepower 4-cylinder
WEIGHT	Breaks down to 2,000lb lifts
WIRELINE ASSEMBLIES	Level wind winch 1,500m 3/16" wireline capacity Rotzler swivel rod hoist
FEED FRAME	UHMW slide saddle 48" mast dump Proprietary feed frame design internally reinforced 45 to 90 degree operational angles 50,000 lbs of pull back
HEAD & FOOT CLAMP	H heads available P foot clamps and H drill head
GUARDING	Full guarding package available for all applications Interlock switch for safe drilling operation
HYDRAULIC SYSTEM	Air-cooled hydraulics system Hydraulic pilot controls Splitter box pump drive system Rexroth and Kawasaki triple pump design Synchronized head and foot clamp with options to isolate functions

FEATURES



Dash Panel



Air Cooler



Mast Dump



Engine

PLATFORM SPECIFICATIONS

TRACKS	CAT 312 steel track system
WEIGHT	20,000lb overall weight
DIMENSIONS	Shipping: 92" wide x 180" long x 101" tall Operational: 155" wide x 218" long x 120" tall
REMOTE CONTROL SYSTEM	12v wireless remote for electric over hydraulic function
FUEL AND MUD SYSTEM	250L double walled fuel tank 500L single mud tank systems with slide-in mixer

FEATURES



Removeable undercarriage



312 steel cat tracks



Leveling cylinders



Drop down walkways



Integrated drill mounts and drip tray



Remote control hydraulic operation



Hydraulic recovery winch

OPTIONS

- X-Spec P Head W. Funk Trans and P Rod Clamp "Christensen"
- AVD P Head W. Funk Trans & P Rod Clamp "Boyles"
- Mirow B-20 "H" Head with P Rod Clamp "Boyles"
- Level Wind Winch with Guards
- Rod Hoist Winch
- Fold down walkway on drillers side to access engine/power pack
- Custom walkway options
- Hydraulic winch

DEPTH CAPACITY BASED ON ROD WEIGHT AT 75% SAFETY FACTOR

Rod Size	Depth Capacity in Meters	Depth Capacity in Feet
B	2829	8950
N	2181	7160
H	1479	4870
P	978	3200



